ID Infinity Drain




S-LTIFAS 99 Series LOW PROFILE

SITE SIZABLE STAINLESS STEEL CHANNEL

- S-LTIFAS 9936 36" Complete Kit
- S-LTIFAS 9948 48" Complete Kit
- S-LTIFAS 9960 60" Complete Kit
- S-LTIFAS 9980 72" Complete Kit
- S-LTIFAS 9996 96" Complete Kit

Features

- Modify length and outlet location on site
- Indoor or outdoor use
- 16 gauge. 304L Stainless steel channel
- 12 gauge. 304L Stainless steel Tile Insert Frame
- Works with 3" clamp down floor with 4" throat/strainer size (included)
- NOT INTENDED for installation across a barrier-free threshold
- Compatible with: PVC Liner, Rubber Liner (Chloraloy ®), Hot Mop, Lead Pan, Copper Pan, or Fiberglass
- Flow rate 21 gpm per outlet
 - Flow rate measured at outlet only. Measurement does not account for water in channel or sheeting on shower floor.
 - Additional outlets can be added and combined into a larger waste line to increase flow rates



Care & Maintenance

S-LTIFAS 99 stainless steel linear drain top grates are made of 304L stainless steel. This material is non-porous, hygienic, rust-free and extremely durable. Bar Keepers Friend® and Soft Scrub® are commonly available products that can be used to protect and clean your Satin Stainless drain cover. For stains that have been left for an excessive amount of time, stronger cleaning agents such as Compound 302® may be needed. For all finishes we recommend using mild soap and a soft cloth for cleaning. DO NOT use any abrasive cleaners, scrub pads or allow household cleaning agents, such as bleach, to sit on the drain cover for a long period of time. Stainless steel does not rust. External factors, such as contamination from other highly ferrous metals, built up road salt, sea salt, or chlorine may have caused "surface" rust which can be removed using Barkeepers Friend®, Soft Scrub®, or Steel Brite Cleaner. Always follow the directions on the bottle. Follow proper maintenance procedures to prevent excessive surface rust. In areas of frequent exposure to salt, chlorine, and other chemical compounds, maintenance of the stainless grates should be performed at least 2-3 times per year.

Infinity Drain 145 Dixon Avenue Amityville, NY 11701 Phone: 516.767.6786 Fax: 516.740.3066 www.Infinity Drain.com








NOTE: Installer must verify all rough-in dimensions prior to installation and consult local and national codes. Conformity and compliance to local and national codes are the responsibility of the installer.

ID Infinity Drain



Model Number	Complete Kit Contents	A Maximum Overall Length	B Maximum Grate Length	C (Minimum Height Above Waterproofing) * All heights can be adjusted upwards an additional 1-1/4"
S-TIFAS 9940-I S-TIFAS 9940-A S-TIFAS 9940-P	1 - RA 6536 Tile Insert Frame 1 - LC 6528 Stainless Steel Channel 1 - LC 99 8" Outlet Section Stainless Steel 2 - GJS 65 Stainless Steel Joiner Strip 1 - ZSIKA M-1 Sealant 2 - CT 36 Channel Trim 1 - HMK-A: 1 - AKEY Lift Out Key 1 - 4" Throat, 3" No Hub Outlet, Drain Body (CDI 43 W/CDA 43 W/CDP 43 W)	36"	35 7/8"	With CDI 43 W: 1 13/16" With CDA 43 W: 1 13/16" With CDP 43 W: 1 13/16"
S-TIFAS 9948-I S-TIFAS 9948-A S-TIFAS 9948-P	1 - RA 6548 Tile Insert Frame 1 - LC 6540 Stainless Steel Channel 1 - LC 99 8" Outlet Section Stainless Steel 2 - GJS 65 Stainless Steel Joiner Strip 1 - ZSIKA M-1 Sealant 2 - CT 48 Channel Trim 1 - HMK-A: 1 - AKEY Lift Out Key 1 - 4" Throat, 3" No Hub Outlet, Drain Body (CDI 43 W/CDA 43 W/CDP 43 W)	48"	47 7/8"	With CDI 43 W: 1 13/16" With CDA 43 W: 1 13/16" With CDP 43 W: 1 13/16"
S-TIFAS 9960-I S-TIFAS 9960-A S-TIFAS 9960-P	1 - RA 6560 Tile Insert Frame 1 - LC 6552 Stainless Steel Channel 1 - LC 99 8" Outlet Section Stainless Steel 2 - GJS 65 Stainless Steel Joiner Strip 1 - ZSIKA M-1 Sealant 2 - CT 36 Channel Trim 1 - HMK-A: 1 - AKEY Lift Out Key 1 - 4" Throat, 3" No Hub Outlet, Drain Body (CDI 43 W/CDA 43 W/CDP 43 W)	60"	59 7/8"	With CDI 43 W: 1 13/16" With CDA 43 W: 1 13/16" With CDP 43 W: 1 13/16"

Finishes

□ Satin Stainless (SS) □ P

□ Polished Stainless (PS)

□ Oil Rubbed Bronze (ORB)


☐ Satin Bronze (SB)

□ Matte Black (BK)

Infinity Drain 145 Dixon Avenue Amityville, NY 11701 Phone: 516.767.6786 Fax: 516.740.3066 www.Infinity Drain.com

FM604-01-22






CANADA - CSA B 125.2 USA - ASME A112.18.2



NOTE: Installer must verify all rough-in dimensions prior to installation and consult local and national codes. Conformity and compliance to local and national codes are the responsibility of the installer.

D Infinity Drain



Model Number	Complete Kit Contents	A Maximum Overall Length	B Maximum Grate Length	C (Minimum Height Above Waterproofing) * All heights can be adjusted upwards an additional 1-1/4"
S-LTIFAS 9972-I S-LTIFAS 9972-A S-LTIFAS 9972-P	2 - RA 6536 Tile Insert Frame 1 - LC 6564 Stainless Steel Channel 2 - LC 99 8" Outlet Section Stainless Steel 4 - GJS 65 Stainless Steel Joiner Strip 1 - ZSIKA M-1 Sealant 2 - CT 72 Channel Trim 1 - HMK-A: 1 - AKEY Lift Out Key 2 - 4" Throat, 3" No Hub Outlet, Drain Body (CDI 43 W/CDA 43 W/CDP 43 W)	72"	35 7/8" (x 2)	With CDI 43 W: 1 13/16" With CDA 43 W: 1 13/16" With CDP 43 W: 1 13/16"
S-LTIFAS 9996-I S-LTIFAS 9996-A S-LTIFAS 9996-P	2 - RA 6536 Tile Insert Frame 1 - LC 6564 Stainless Steel Channel 2 - LC 99 8" Outlet Section Stainless Steel 4 - GJS 65 Stainless Steel Joiner Strip 1 - ZSIKA M-1 Sealant 2 - CT 72 Channel Trim 1 - HMK-A: 1 - AKEY Lift Out Key 2 - 4" Throat, 3" No Hub Outlet, Drain Body (CDI 43 W/CDA 43 W/CDP 43 W)	96"	47 7/8" (x 2)	With CDI 43 W: 1 13/16" With CDA 43 W: 1 13/16" With CDP 43 W: 1 13/16"

Optional Components				
UCP 4	Universal 4" Clamping Plate			
TNRN-4	4" Cast Iron Extension Nipple			
Add Clamp Down Drain				
CDA 42	Clamp Down Drain ABS			
CDI 42	Clamp Down Drain Cast Iron			
CDP 42	Clamp Down Drain PVC			
CDA 43 W	Clamp Down Drain ABS			
CDI 43 W	Clamp Down Drain Cast Iron			
CDP 43 W	Clamp Down Drain PVC			

MADE IN THE USA

ID INFINITY DRAIN CANADA - CSA B 125.2 USA - ASME A112.18.2

RA 6536

RA 6548

RA 6560

SC 6548

SC 6596

LC 6528

LC 6540

LC 6552

LC 6564

LC 6588



Available components for longer lengths

48" Stainless Open Ended Channel

96" Stainless Open Ended Channel

28" Stainless Closed Channel

40" Stainless Closed Channel

52" Stainless Closed Channel

64" Stainless Closed Channel

88" Stainless Closed Channel

SE 65

GJS 65

SLA 65

LF 99

CT 36

CT 48

CT 60

CT 72

CT 96

36" Tile Insert Frame

48" Tile Insert Frame

60" Tile Insert Frame

dimensions prior to installation and consult local and national codes. Conformity and compliance to local and national codes are the responsibility of the installer.

NOTE: Installer must verify all rough-in

2" Stainless Steel End Section

Stainless Steel 90° Angle Joiner

8" Stainless Steel Outlet Section

Stainless Steel Joiner Strip

36" Channel Trim

48" Channel Trim

60" Channel Trim

72" Channel Trim

96" Channel Trim

FM604-01-22